



Professional ———— Metallic Scales

BELPROFILE Rondo

Round scales used to emphasize architectural details integrated into the roof.

- Suitable for special architectural works.
- Ensure the preservation of a traditional look.
- Highlight the elements on which attention is drawn.
- Fixed by hidden fasteners.
- Very attractive visual effect.





BELPROFILE

ONE ROOF. MORE GENERATIONS


Professional



Metallic Scales



BELPROFILE Rondo



pre-painted hot-dip galvanized steel

thickness **0,55 mm**

finish	warranty	lifespan	weight	Zinc protection layer	protective paint layer
MagneZinc	30 years	100 years	4,3 kg/m²	120 g/m²	-

Provides additional protection, being three times more resistant to corrosion as compared to zinc-coated steel.



Natur

thickness **0,60 mm**

RainDrop	30 years	100 years	4,4 kg/m²	275 g/m²	SPE 35 + 35 µm
-----------------	-----------------	------------------	-----------------------------	----------------------------	-----------------------

Super-polyester coating, with greater color stability in time and enhanced scratch resistance.



RAL 3005



RAL 3009




RAL 3011



RAL 7016



RAL 7024



RAL 8004



RAL 8017



RAL 8019




RAL 9005



RAL 9010

PrinTech	30 years	100 years	4,4 kg/m²	275 g/m²	HDP 35 + 15 µm
-----------------	-----------------	------------------	-----------------------------	----------------------------	-----------------------

The best-performing sheet-metal coating product, it is applied in 10 layers and offers the longest lifespan.



Weathered



Korten




HairLine
Copper

aluminum

 thickness **0,60 mm**

finish	warranty	lifespan	weight	Zinc protection layer	protective paint layer
Embossed	40 years	100 years	1,65 kg/m²	-	25 µm

Matte polyester paint, with the structure applied directly to the aluminum sheet, offers very high stability over time.



RAL 7016



RAL 8019

 thickness **0,70 mm**

SunClear	40 years	100 years	1,9 kg/m²	-	25 µm
-----------------	-----------------	------------------	-----------------------------	---	--------------

Glossy polyester paint, the traditional version of protection for metal products.



RAL 7016




RAL 8019



RAL 9010

ACCESSORIES AND AUXILIARIES METALLIC SCALES




METALLIC SCALES INSTALATION PRINCIPLES

Sheet-metal work components for rainwater collection shall be installed before positioning the metal tile panels


01 ROOF STRUCTURE

The scales have the advantage that they can be mounted both on an inclined plane and on a vertical plane.




02 THE SEPARATION MEMBRANE WITH DIFFUSION LAYER

It is mounted on the deck and over the gutter apron and has the role of preventing direct contact of the sheet metal panels with the diffusion foil, which can be wet due to condensation.




03 VALLEY

It is fixed with clamps, its drilling is forbidden. It is mounted at the intersection of two sides of the roof.




04 METALLIC SCALES MOUNTING

The assembly of the scales is done in rows. It is recommended that the surface be drawn before mounting to ensure that the scales will be perpendicular to the direction of water flow. The assembly is done with 4 mm space between adjacent scales. They are fixed with woodscrews or using ribbed nails.




05 RIDGE ANGLE

It is used to close the side of the roof.



06 HIGH HOOKING PROFILE

It is used to mount ridges, on either side of them. Its assembly on panels is done mechanically with the help of pop-rivets, using double-sided butyl tape that acts as a gasket. The ridge will be fixed in this profile without directly piercing the panel.



07 STRAIGHT RIDGE

It is mounted over the high hooking profile or over the "Z" profile.




08 SNOW CUTTER

The element is fixed over the scale and its tail is covered by the upper scale.




MINIMUM SET OF TOOLS REQUIRED FOR ASSEMBLY


SPIRIT LEVEL




METER




CARPENTRY PENCIL




CORDLESS SCREWDRIVER



SHEET METAL PROFILE PLIERS




ELECTRIC JIGSAW




HACKSAW




SHEET METAL SHEARS



SAFETY SOFT-FACED HAMMER



ANGLE GRINDER



VERY IMPORTANT!

BELPROFILE products (metal tiles, corrugated iron, drainage systems and accessories) are shipped on wooden pallets to avoid bending or hitting the products. Store in dry and ventilated areas, protected from sun, moisture and aggressive substances (eg: acids, salt, wet concrete). The tile is stored on wooden pallets, placed one meter away. It is not recommended to overlap more than 3 pallets of 150 tile sheets each. Pallets must be covered but good ventilation will be provided to prevent condensation. The storage of the tile outside must be only temporary, not more than 72 hours and in an inclined plane of at least 10°.

Metallic scales handling

Rombo and Rondo metal scales are wrapped in packs of 10 pieces. When handling them, personal protection measures will be taken regarding the maximum displacement weight of 25 Kg.

Cutting

Special tools will be used in smithery (electric scissors or manual). It is strictly forbidden to cut with the help of an angle grinder.

Cleaning after cutting

The filing resulting from the cutting is removed with a soft brush.

Paint for retouching

It is used to cover accidental scratches and to protect cut edges. Do not use on large surfaces because color differences may occur.